

# TFSP AL 0,6/1kV

HD 603 S1 Part 5-M



## XLPE insulated and PVC sheathed power cable with concentric copper conductor



### CONSTRUCTION

<b>Conductors:</b>	plain soft aluminium (annealed after stranding) circular or circular compacted stranded conductor class 2 (AFR) or stranded sector – shaped conductor class 2 (AFV) acc. to EN 60228
<b>Insulation:</b>	XLPE compound type DIX10 acc. to HD 603.1
<b>Inner covering:</b>	Polypropylene tape
<b>Concentric conductor:</b>	round copper wires and copper tape with polyester bedding
<b>Sheath:</b>	PVC compound type DMV16 acc. to HD 603.1

### CHARACTERISTIC

<b>Colour of sheath:</b>	grey RAL 7037
<b>Core identification:</b>	3-core: brown, black, grey 4-core: blue, brown, black, grey
<b>Maximum conductor operating temperature:</b>	+90°C
<b>Lowest ambient temperature for fixed installation:</b>	-30°C
<b>Lowest installation temperature:</b>	-10°C
<b>Maximum short-circuit conductor temperature:</b>	+ 250°C
<b>Minimum bending radius:</b>	12 x D, D – overall diameter
<b>Max. permissible tensile stress with cable grip for AL-conductor:</b>	30 N/mm <sup>2</sup>
<b>Test voltage:</b>	3,5kV
<b>Flame retardant:</b>	IEC 60332-1-2

### APPLICATIONS

XLPE insulated and sheathed power cables for the supply of electrical energy. Special for installations in the open air, in underground and water, indoors, in cable ducts. The concentric conductor is allowed to use as neutral, protective or earthed conductor. Simultaneously, this also is permitted to apply as a screen for example earth-connected protection against contact.

<b>Standard length cable packing</b>	500 or 1000m on drums. Other forms of packing and delivery are available on request
--------------------------------------	--

# TFSP AL 0,6/1kV

HD 603 S1 Part 5-M



Number and cross-sectional area of conductor	Approximate overall diameter	Approximate net weight of cables	Maximum conductor /concentric conductor resistance at temperature 20°C
<b>n x mm<sup>2</sup></b>	<b>mm</b>	<b>kg/km</b>	<b>Ω/km</b>
3x240AFV/70	49,5	3458	0,125/0,268
4x25FR/10	26,2	736	1,2/1,83
4x150FV/50	45,5	2851	0,206/0,387



All the information contained in this document - including tables and diagrams - is given in good faith and believed to be correct at the time of publication. The information does not constitute a warranty nor representation for which TELE-FONIKA Kable assumes legal responsibility. TELE-FONIKA Kable reserves rights to introduce changes to the document at any time.